

Appendix 14.2

Carbon Balance Input Data

Contents

Core Input Data

1

Core Input Data

Core input data

ENTER INPUT DATA HERE! VALUES SHOULD ONLY BE CHANGED ON THIS SHEET. **DO NOT USE EXAMPLE VALUES AS DEFAULTS!** ENTER YOUR OWN VALUES THAT ARE SPECIFIC TO YOUR PARTICULAR SITE.

Note: The input parameters include some variables that can be specified by default values, but others that must be site specific. Variables that can be taken from defaults are marked with purple tags on left hand side.

Click here to move to Payback Time [Click here](#)

Click here to return to Instructions [Click here](#)

Input data	Expected values		Possible range of values	
	Enter expected value here	Record source of data	Enter minimum value here	Record source of data
Windfarm characteristics				
Dimensions				
No. of turbines	14		14	
Lifetime of windfarm (years)	40		40	
Performance				
Power rating of turbines (turbine capacity) (MW)	6.8		6.8	
Capacity factor	Direct input of capacity fa		Direct input of capacity fa	
Enter estimated capacity factor (percentage efficiency)	25.4		22.3	
Backup				
Extra capacity required for backup (%)	5		5	
Additional emissions due to reduced thermal efficiency of the reserve generation (%)	10		10	
Carbon dioxide emissions from turbine life - (eg. manufacture, construction, decommissioning)	Calculate wrt installed ca		Calculate wrt installed ca	
Characteristics of peatland before windfarm development				
Type of peatland	Acid t		Acid t	
Average annual air temperature at site (°C)	9.6		6.59	
Average depth of peat at site (m)	0.52		0.48	
C Content of dry peat (% by weight)	50		44	
Average extent of drainage around drainage features at site (m)	5.00		3.00	
Average water table depth at site (m)	0.50		0.30	
Dry soil bulk density (g cm ⁻³)	0.12		0.09	
Characteristics of bog plants				
Time required for regeneration of bog plants after restoration (years)	30		20	

Note: Capacity factor. The capacity factor of any power plant is the proportion of energy produced during a given period with respect to the energy that would have been produced had the wind farm been running continually and at maximum output (DECC (2004); see also www.bwea.com/ref/capacityfactors.html).

Capacity Factor = Electricity generated during the period [kWh] / (Installed capacity [kW] x number of hours in the period [h]).

We recommend that a site-specific capacity factor site-should be used (as measured during planning stage), and should represent the average emission factor expected over the lifetime of the windfarm, accounting for decline in efficiency with age (Hughes, 2012). The 5 year average capacity factor (or 'load factor') for UK onshore wind between 2010 and 2014, based on average beginning and end of year capacity, was 29.2% (DUKES, 2015).

Note: Extra capacity required for backup. If 20% of national electricity is generated by wind energy, the extra capacity required for backup is 5% of the rated capacity of the wind plant (Dale et al 2004). We suggest this should be 5% of the actual output. If it is assumed that less than 20% of national electricity is generated by wind energy, a lower percentage should be entered (0%). The House of Lords Economic Affairs Committee report on The Economics of Renewable Energy (Parliamentary Business, 2008) notes that to cover peak demand a '20% margin of extra capacity has been sufficient to keep the risk of a power cut due to insufficient generation at a very low level.' The estimate provided by BERR was a range of 10% to 20% of installed capacity of wind energy. E.ON is reported as proposing that the capacity credit of wind power should be 8%, and The Renewable Energy Foundation proposed the use of the square root of the wind capacity (in GW) as conventional capacity (e.g. 36 GW of wind plant to match 6 GW of conventional plant).

Note: Extra emissions due to reduced thermal efficiency of the reserve power generation ≈ 10% (Dale et al 2004).

Note: Emissions from turbine life. If total emissions for the windfarm are unknown, emissions should be calculated according to turbine capacity. The normal range of CO₂ emissions is 394 to 8147 t CO₂ / MW (White & Kulcinski, 2000; White, 2007).

Note: Type of peatland. An 'acid bog' is fed primarily by rainwater and often inhabited by sphagnum moss, thus making it acidic (Stoneman & Brooks, 1997). A 'fen' is a type of wetland fed by surface and/or groundwater (McBride et al., 2011).

Note: Time required for regeneration of previous habitat. Loss of fixation should be assumed to be over lifetime of windfarm only. This time could be longer if plants do not regenerate. The requirements for after-use planning include the provision of suitable refugia for peat-forming vegetation, the removal of structures, or an assessment of the impact of leaving them in situ.

Carbon accumulation due to C fixation by bog plants in undrained peats (tC ha ⁻¹ yr ⁻¹)	0.25	0.12	0.31	Methods used to reinstate the site will affect the likely time for regeneration of the previous habitat. This time could also be shorter if plants regenerate during lifetime of windfarm. If so, enter number of years estimated for regeneration.
Forestry Plantation Characteristics				
Method used to calculate CO ₂ loss from forest felling	Enter simple data ▼	Enter simple data ▼	Enter simple data ▼	Note: <u>Carbon fixation by bog plants</u> . Apparent C accumulation rate in peatland is 0.12 to 0.31 t C ha ⁻¹ yr ⁻¹ (Turunen et al., 2001; Botch et al., 1995). The SNH guidance uses a value of 0.25 t C ha ⁻¹ yr ⁻¹ .
Area of forestry plantation to be felled (ha)	72.55	65.3	79.8	
Average rate of carbon sequestration in timber (tC ha ⁻¹ yr ⁻¹)	3.60	3.60	3.60	
Counterfactual emission factors				
To update counterfactual emission factors from the web Click here (not yet operational)				Note: <u>Area of forestry plantation to be felled</u> . If the forestry was planned to be removed, with no further rotations planted, before the windfarm development, the area to be felled should be entered as zero.
Coal-fired plant emission factor (t CO ₂ MWh ⁻¹)	0.319	0.319	0.319	Note: <u>Plantation carbon sequestration</u> . This is dependent on the yield class of the forestry. The SNH technical guidance assumed yield class of 16 m ³ ha ⁻¹ yr ⁻¹ , compared to the value of 14 m ³ ha ⁻¹ yr ⁻¹ provided by the Forestry Commission. Carbon sequestered for yield class 16 m ³ ha ⁻¹ yr ⁻¹ = 3.6 tC ha ⁻¹ yr ⁻¹ (Cannell, 1999).
Grid-mix emission factor (t CO ₂ MWh ⁻¹)	0.09	0.09	0.09	
Fossil fuel-mix emission factor (t CO ₂ MWh ⁻¹)	0.251	0.251	0.251	Note: <u>Coal-Fired Plant and Grid Mix Emission Factors</u> . Coal-fired plant emission factor (EF) from electricity supplied in 2014 = 0.093 t CO ₂ MWh ⁻¹ ; Grid-Mix EF for 2014 = 0.394 t CO ₂ MWh ⁻¹ . Source = DUKES, 2015b.
Borrow pits				
Number of borrow pits	7	7	7	
Average length of pits (m)	121	105	138	
Average width of pits (m)	121	105	138	
Average depth of peat removed from pit (m)	0.66	0.57	0.74	Note: <u>Fossil Fuel-Mix Emission Factor</u> . The emission factor from electricity supplied in 2014 from all fossil fuels = 0.642 t CO ₂ MWh ⁻¹ . Source = DUKES, 2015b.
Foundations and hard-standing area associated with each turbine				
Method used to calculate CO ₂ loss from foundations and hard-standing	Rectangular with vertice ▼	Rectangular with vertice ▼	Rectangular with vertice ▼	...
Average length of turbine foundations (m)	40.5	38	33	...
Average width of turbine foundations (m)	40.5	38	32	
Average depth of peat removed from turbine foundations (m)	0.86	0.54	1.18	
Average length of hard-standing (m)	186	186	186	
Average width of hard-standing (m)	70	63	77	
Average depth of peat removed from hard-standing (m)	0.92	0.87	0.97	
Access tracks				
Total length of access track (m)	18590	16731	20449	Note: <u>Total length of access track</u> . If areas of access track overlap with hardstanding area, exclude these from the total length of access track to avoid double counting of land area lost.
Existing track length (m)	4120	3708	4532	
Length of access track that is floating road (m)				
Floating road width (m)				Note: <u>Floating road depth</u> . Accounts for sinking of floating road. Should be entered as the average depth of the road expected over the lifetime of the windfarm. If no sinking is expected, enter as zero.
Floating road depth (m)				
Length of floating road that is drained (m)				Note: <u>Length of floating road that is drained</u> . Refers to any drains running along the length of the road.
Average depth of drains associated with floating roads (m)				
Length of access track that is excavated road (m)	18590	16731	20449	
Excavated road width (m)	19.56	20.9	22.12	
Average depth of peat excavated for road (m)	0.85	0.76	0.93	
Length of access track that is rock filled road (m)				Note: <u>Rock filled roads</u> . Rock filled roads are assumed to be roads where no peat has been removed and rock has been placed on the surface and allowed to settle.

Length of access track that is rock filled road (m)						removed and rock has been placed on the surface and allowed to settle.
Rock filled road width (m)						
Rock filled road depth (m)						
Length of rock filled road that is drained (m)						
Average depth of drains associated with rock filled roads (m)						
Cable Trenches						
Length of any cable trench on peat that does not follow access tracks and is lined with a permeable medium (eg. geotextile) (m)						
Average depth of peat cut for cable trenches (m)						Note: Depth of peat cut for cable trenches. In shallow peats, the cable trenches may be cut below the peat. To avoid overestimating the depth of peat affected by the cable trenches, only enter the depth of the peat that is cut.
Additional peat excavated (not already accounted for above)						
Volume of additional peat excavated (m ³)	22615		15524.9		32333.9	
Area of additional peat excavated (m ²)	22300.0		19170.0		26030.0	Note: Peat Landslide Hazard. It is assumed that measures have been taken to limit damage (Scottish Executive, 2006, Peat Landslide Hazard and Risk Assessments. Best Practice Guide for Proposed Electricity Generation Developments. Scottish Executive, Edinburgh, pp. 34-35) so that C losses due to peat landslide can be assumed to be negligible. Link: http://www.scotland.gov.uk/Publications/2006/12/21162303/1 .
Peat Landslide Hazard						
Weblink: Peat Landslide Hazard and Risk Assessments: Best Practice Guide for Proposed Electricity Generation Developments						
Improvement of C sequestration at site by blocking drains, restoration of habitat etc						
Improvement of degraded bog						
Area of degraded bog to be improved (ha)						
Water table depth in degraded bog before improvement (m)						
Water table depth in degraded bog after improvement (m)						
Time required for hydrology and habitat of bog to return to its previous state on improvement (years)						
Period of time when effectiveness of the improvement in degraded bog can be guaranteed (years)						Note: Period of time when improvement can be guaranteed. This guarantee should be absolute. Therefore, if you enter a value beyond the lifetime of the windfarm you should provide strong supporting evidence that this improvement can be guaranteed for the full period given. This includes the time requirement for the improvement to become effective. For example if time required for hydrology and habitat to return to its previous state is 10 years and the restoration can be guaranteed over the lifetime of the windfarm (25 years), the period of time when the improvement can be guaranteed should be entered as 25 years, and the improvement will be effective for (25 - 10) = 15 years.
Improvement of felled plantation land						
Area of felled plantation to be improved (ha)						
Water table depth in felled area before improvement (m)						
Water table depth in felled area after improvement (m)						
Time required for hydrology and habitat of felled plantation to return to its previous state on improvement (years)						
Period of time when effectiveness of the improvement in felled plantation can be guaranteed (years)						Note: Period of time when improvement can be guaranteed. This guarantee should be absolute. Therefore, if you enter a value beyond the lifetime of the windfarm you should provide strong supporting evidence that this improvement can be guaranteed for the full period given. This includes the time requirement for the improvement to become effective. For example if time required for hydrology and habitat to return to its previous state is 10 years and the restoration can be guaranteed over the lifetime of the windfarm (25 years), the period of time when the improvement can be guaranteed should be entered as 25 years, and the improvement will be effective for (25 - 10) = 15 years.
Restoration of peat removed from borrow pits						
Area of borrow pits to be restored (ha)						
Depth of water table in borrow pit before restoration with respect to the restored surface (m)						

Depth of water table in borrow pit after restoration with respect to the restored surface (m)						Note: Period of time when improvement can be guaranteed. This guarantee should be absolute. Therefore, if you enter a value beyond the lifetime of the windfarm you should provide strong supporting evidence that this improvement can be guaranteed for the full period given. This includes the time requirement for the improvement to become effective. For example if time required for hydrology and habitat to return to its previous state is 10 years and the restoration can be guaranteed over the lifetime of the windfarm (25 years), the period of time when the improvement can be guaranteed should be entered as 25 years, and the improvement will be effective for (25 - 10) = 15 years.
Time required for hydrology and habitat of borrow pit to return to its previous state on restoration (years)						
Period of time when effectiveness of the restoration of peat removed from borrow pits can be guaranteed (years)						
Early removal of drainage from foundations and						Note: Period of time when improvement can be guaranteed. This is assumed to be the lifetime of the windfarm as restoration after windfarm decommissioning is already accounted for in restoration of the site
Water table depth around foundations and hardstanding before restoration (m)	0.50		0.30		0.70	
Water table depth around foundations and hardstanding after restoration (m)	0.30		0.10		0.50	
Time to completion of backfilling, removal of any surface drains, and full restoration of the hydrology (years)	3		2		5	Note: Restoration of site. If the water table at the site is returned to its original level or higher on decommissioning, and habitat at the site is restored, it is assumed that C losses continue only over the lifetime of the windfarm. Otherwise, C losses from drained peat are assumed to be 100%.
Restoration of site after decommissioning Will the hydrology of the site be restored on decommissioning?	Yes		Yes		Yes	
Will you attempt to block any gullies that have formed due to the windfarm?	Yes		Yes		Yes	
Will you attempt to block all artificial ditches and facilitate rewetting?	Yes		Yes		Yes	Note: Choice of methodology for calculating emission factors. The IPCC default methodology is the internationally accepted standard (IPCC, 1997). However, it is stated in IPCC (1997) that these are rough estimates, and "these rates and production periods can be used if countries do not have more appropriate estimates". Therefore, we have developed more site specific estimates for use here based on work from the Scottish Government funded ECOSSE project (Smith et al, 2007. ECOSSE: Estimating Carbon in Organic Soils - Sequestration and Emissions. Final Report. SEERAD Report. ISBN 978 0 7559 1498 2. 166pp.).
Will the habitat of the site be restored on decommissioning?	No		No		No	
Will you control grazing on degraded areas?	No		No		No	
Will you manage areas to favour reintroduction of species	No		No		No	
Choice of methodology for calculating emission factors	Site specific (required for planning applications)					

Core input data

ENTER INPUT DATA HERE! VALUES SHOULD ONLY BE CHANGED ON THIS SHEET. DO NOT USE EXAMPLE VALUES AS DEFAULTS! ENTER YOUR OWN VALUES THAT ARE SPECIFIC TO YOUR PARTICULAR SITE.

Note: The input parameters include some variables that can be specified by default values, but others that must be site specific. Variables that can be taken from defaults are marked with purple tags on left hand side.